

HELIX 158X[®]

ORDER CODE: HX-158x-II



WIRELESS PORTABLE PA SYSTEM



Features

- Includes Class-D digital power amplifier delivering 100W to the internal 8" full range speaker and 100W to an external speaker.
- 2 power modes: Internal Rechargeable battery & DC jack.
- All-in-one! Easy to operate in both indoors and outdoors.
- Comes with built-in Bluetooth player.
- Up to 6 hours with Lead-Acid battery.
- User friendly battery compartment design for simple battery replacement.
- High efficiency system; compact cabinet and efficient 8" full range speaker for live performance.
- Up to 2 diversity receiver modules with 100 selectable frequencies in each system (optional).
- Automatic Digital limiter with 6 LED indicators prevents output distortion.
- 2-band equaliser, BASS/TREBLE and MASTER volume control.
- AUX OUT (6.3mm jack) for external audio recording.
- LINE IN (3.5mm jack) with individual volume control.
- MICROPHONE 1 and 2 are XLR/6.3mm combo jack connectors for wired microphone inputs with individual volume control and a MIC/LINE level switch.
- REVERB control for wired and wireless microphones.
- AUX OUT (6.3mm jack) and SPEAKER OUT (6.3mm jack) for external passive speakers.
- Smart charging circuit with 4-step LED battery indicators and charging LED.
- Tripod stand mountable with HX-ST.

Specifications

Model	HELIX-158X-II
Output power	150W (Class-D)
Speaker system	8" full range
Audio input	Mic in x 2 (COMBO), Line in (3.5mm)
Audio output	Aux out, External speaker
T.H.D.	< 0.5%
Frequency response	50Hz-20KHz±3dB
Antenna	Built-in
Power supply	100-240V AC / 30-32V DC, 4A
Battery type	Lead-Acid
Battery specifications	12V, 5Ah
Battery quantity	2
Battery Indicator	4 LED indicators
Operating time	5-6 hrs in music, >10 hrs in speech
Charging time	about 6 hrs
Dimensions (mm)	424 (H) x 290 (W) x 250 (D)
Weight (kg)	10.8

* NOTE: The above specifications are subject to change without prior notice.